



TJS-ANBC20

TJS-ANBC20

General Features:

- IP66 Metal Bullet Camera**
- 3.6 mm fixed**
- 36 IR LED's**
- Auto Day & Night**
- Auto White Balance**
- Auto Gain Control**

Dimensions:

80 x 90 x 160 mm

**Colour:
White**

Model:	TJS-ANBC20EE7	TJS-ANBC20CM12	TJS-ANBC20CM8
Camera Type:	IP66 Waterproof Bullet Camera		
Image Sensor:	Sony EFFIO-E	Color 1/3" CMOS/DIS	Color 1/4" CMOS/DIS
Effective Pixels:	PAL: 976 (H) x 582 (V) NTSC: 976 (H) x 494 (V)	PAL: 1305 (H) x 1049 (V) NTSC: 1305 (H) x 1049 (V)	PAL: 960 (H) x 480 (V) NTSC: 960 (H) x 480 (V)
Sensing Area:	4,9mm x 3,7mm		
Signal System:	PAL / NTSC		
Horizontal Resolution:	700TVL	1200TVL	800TVL
Min. Illumination:	0,01 Lux (Colour) 0 Lux (IR ON)	0,01 Lux (Colour) 0 Lux (IR ON)	0,01 Lux (Colour) 0 Lux (IR ON)
Lens:	3,6mm Fixed Lens		
Signal to Noise Ratio:	>52dB	>50dB	>50dB
OSD:	YES	YES	NO
OSD Function:	Manual / DC Lens Shutter Picture Adjust Mirror Day & Night DNR / ART BLC-HLC Motion Detection Privacy Masking	Manual / DC Lens Shutter Picture Adjust Mirror DNR / ART BLC-HLC Motion Detection Privacy Masking	NO
Electric Shutter:	PAL: 1/50 ~ 1/10.000 sec. Auto (NTSC) 1/60 ~ 1/10.000 sec.		
Digital Day & Night:	Auto		
White Balance:	Auto		
Automatic Gain Control:	Auto		
IR:	>30m (36 IR-LED φ5)		
IR Wavelength:	850 nm		
IP Rating:	IP66		
Connectors:	Power: DC Power Jack Video Output: BNC		
Video Output Level:	1.0Vp-p Composite Video Output, 75Ω		
Power Supply:	DC12V ± 10%		
Power Consumption:	130mA, 400mA (IR ON)	130mA, 500mA (IR ON)	
Dimensions:	80mm x 90mm x 160mm		
Colour:	White		
Weight:	<1.0 Kg		
Operating Temperature:	-10°C ~ 50°C		