



TJS-ANBC17

TJS-ANBC17

General Features:

- IP66 Metal Bullet Camera
- 2,8 - 12 mm varifocal
- 60 IR LED's
- Auto Day & Night
- Auto White Balance
- Auto Gain Control

Dimensions:

80 x 90 x 160 mm

Colour:

Grey

| Model: | TJS-ANBC17EV8 | TJS-ANBC17EE7 | TJS-ANBC17CM12 | TJS-ANBC17CM8 |
|-------------------------|---|---|--|---|
| Camera Type: | IP66 Waterproof Bullet Camera | | | |
| Image Sensor: | Sony EFFIO-V | Sony EFFIO-E | Color 1/3" CMOS/DIS | Color 1/4" CMOS/DIS |
| Effective Pixels: | PAL: 976 (H) x 582 (V) NTSC: 976 (H) x 494 (V) | PAL: 976 (H) x 582 (V) NTSC: 976 (H) x 494 (V) | PAL: 1305 (H) x 1049 (V) NTSC: 1305 (H) x 1049 (V) | PAL: 960 (H) x 480 (V) NTSC: 960 (H) x 480 (V) |
| Sensing Area: | 4,9mm x 3,7mm | | | |
| Signal System: | PAL / NTSC | | | |
| Horizontal Resolution: | 800TVL | 700TVL | 1200TVL | 800TVL |
| Min. Illumination: | 0,01 Lux (Colour) 0 Lux (IR ON) | 0,01 Lux (Colour) 0 Lux (IR ON) | 0,01 Lux (Colour) 0 Lux (IR ON) | 0,01 Lux (Colour) 0 Lux (IR ON) |
| Lens: | 2,8-12mm Varifocal | | | |
| Signal to Noise Ratio: | >52dB | >52dB | >50dB | >50dB |
| OSD: | YES | YES | YES | NO |
| OSD Function: | ATR-EX2 / 2D-NR / 3D-NR Day & Night / 20 polygon privacy mask E-Zoom (x256) / Slow Shutter Digital Image Stabilizer / BLC-HLC Auto Scene Detect. Funtion Scene Selection Function AF Detector / Motion Detection White Pixel Detection Compensation Lens Shading Compensation Defog / WDR auto Iris | Manual / DC Lens Shutter Picture Adjust Mirror Day & Night DNR / ART BLC-HLC Motion Detection Privacy Masking | Manual / DC Lens Shutter Picture Adjust Mirror DNR / ART BLC-HLC Motion Detection Privacy Masking | NO |
| Electric Shutter: | PAL: 1/50 ~ 1/10.000 sec. Auto (NTSC) 1/60 ~ 1/10.000 sec. | | | |
| Digital Day & Night: | Auto | | | |
| White Balance: | Auto | | | |
| Automatic Gain Control: | Auto | | | |
| IR: | 50m (60 IR-LED ϕ 5) | | | |
| IR Wavelength: | 850 nm | | | |
| IP Rating: | IP66 | | | |
| Connectors: | Power: DC Power Jack Video Output: BNC | | | |
| Video Output Level: | 1.0Vp-p Composite Video Output, 75 Ω | | | |
| Power Supply: | DC12V \pm 10% | | | |
| Power Consumption: | 130mA, 400mA (IR ON) | | 130mA, 500mA (IR ON) | |
| Dimensions: | 80mm x 90mm x 160mm | | | |
| Colour: | Grey | | | |
| Weight: | <1.0 Kg | | | |
| Operating Temperature: | -10 $^{\circ}$ C ~ 60 $^{\circ}$ C | | | |