



TJS-IPBC17

TJS-IPBC17

General Features:

Metal Bullet IP Camera
2,8 - 12 mm Varifocal
42 IR LED's
Auto Day & Night
Auto White Balance
Auto Gain Control
ONVIF 2.0

Dimensions:

80 x 90 x 160 mm

Colour:

Grey

Model:	TJS-IPBC1730	TJS-IPBC1720	TJS-IPBC1713	TJS-IPBC1710
Camera Type:	IP66 Waterproof Bullet Camera			
Image Sensor:	1/3" Aptina AR0330 CMOS	1/2.8" SONY Exmor IMX222 CMOS	1/3" Aptina AR0130 CMOS	1/4" OmniVision OV9712 CMOS
Effective Pixels:	Main Stream: 3.0MP 2048 (H) x 1536 (V) 2.0MP 1920 (H) x 1080 (V)	Main Stream: 1080P 1920 (H) x 1080 (V) 720P 1280 (H) x 720 (V)	Main Stream: 960P 1280 (H) x 960 (V) 720P 1280 (H) x 720 (V)	Main Stream: 720P 1280 (H) x 720 (V)
	Sub Stream: D1 704 (H) x 576 (V) CIF 352 (H) x 288 (V)	Sub Stream: D1 704 (H) x 576 (V) CIF 352 (H) x 288 (V)	Sub Stream: D1 704 (H) x 576 (V) CIF 352 (H) x 288 (V)	Sub Stream: D1 704 (H) x 576 (V) CIF 352 (H) x 288 (V)
Frame Rate	PAL: 20/25fps NTSC: 20/30fps	PAL: 25fps NTSC: 30fps	PAL: 25fps NTSC: 30fps	PAL: 25fps NTSC: 30fps
Resolution:	3.0MP	2.0MP	1.3MP	1.0MP
Min. Illumination:	0,01 Lux (Colour) 0 Lux (IR ON)	0,01 Lux (Colour) 0 Lux (IR ON)	0,01 Lux (Colour) 0 Lux (IR ON)	0,6 Lux (Colour) 0,08 Lux (IR ON)
Lens:	2.8-12mm Varifocal			
Signal to Noise Ratio:	>50dB			
Electric Shutter:	Auto: 1/25 ~ 1/50.000 Manual: 1/30 ~ 1/60.000			
Digital Day & Night:	Auto			
Backlight Compensation:	BLC / HLC			
White Balance:	Auto			
Automatic Gain Control:	Auto			
IR:	40m (42 IR-LED ϕ 5)			
ONVIF:	ONVIF 2.0			
IP Rating:	IP66			
Connectors:	Power: DC Power Jack Network Output: RJ45			
Power Supply:	DC12V \pm 10% / PoE (Optional 802.3 af / 820.3 at)			
Power Consumption:	IR On: 600mA / IR Off <200mA			
Dimensions:				
Colour:	Grey			
Weight:	<1,0Kg			
Operating Temperature:	-10°C ~ 60°C			